

TB-80

Automatic Labeling Machine



Introduction:

- All mechanically operated design with all transmission mechanism in enclosed oil-bath thus ensures smooth running, quiet, low drive and trouble-free operations.
- Conveyor load lower top surface and turn table made of stainless steel for durability and ease in cleaning.
- Good for both individual operation and connection line.
- Small floor space. Compact and easily movable with casters.
- Most suitable for small standard of round bottle labeling in chemical.
- Pharmaceutical, food and beverage industries. The print unit can be added to the product according to the user's need.

| Main Technical Specifications | | | |
|-------------------------------|------------------------------|------------------------------|-----------------------------|
| model | TBL-60 | TB-80 | TB-80D |
| speed | 60 bottles/Min | 80 bottles/Min | 80-160 bottles/Min |
| Width | 40-110 mm | 40-110 mm | 25-60 mm |
| Length | 50-300 mm | 50-130 mm | 25-100 mm |
| Power | AC220V or AC380V, 1.75kW | AC220V or AC380V, 1.5kW | AC220V or AC380V, 1.5kW |
| Dimension | 3000mm(L)X950mm(W)X1200mm(H) | 2100mm(L)X950mm(W)X1000mm(H) | 2270mm(L)X840mm(W)X910mm(H) |
| Weight | 650kg | 550kg | 700kg |