800 Series

Advantage Machinery

Automatic Vertical L-Bar Sealing Machines

The 800 Series Vertical L-Bar Sealing Machines are manufactured with advanced design and innovated technology. The machine is controlled via a PLC which allows the operator to set the different times for the sealing operation, the temperature of the blades and also the length of film that is to be used. The machine has a variable speed conveyor which makes the machine ideal for both manual and automatic feeding. The vertical sealing height is adjustable to the height of the product, allowing for the sealing line to be in the center of the package. The machine is easy to operate and high in efficiency.

Some of the machine features are:

• Quick change over between productions and sizes.

Horizontal and Vertical sensors for the packaging of different products.

• The knives are set on four shafts and the height is mechanically adjusted.

• Solid knife sealing blades make a consistent seal and are long lasting.

• Automatic film advance allows for light weight products to easily be fed through.

Automatic waste removal system.

Extended product heights available.









Model	801	802	803	804
Product Size LxWxH (in)	$(2 \sim 15.75) \times (2 \sim 11) \times (0.1 \sim 6)$	(4 ~ 22) x (2 ~ 18) x (0.1-8.6)	$(7.5 \sim 33) \times (7.5 \sim 25) \times (0.5 \sim 8.6)$	(7.7 ~ 35.3) x (7.7 ~ 28) x (0.5 ~ 12)
Sealing Blade Size (LxW) (in)	17.72 x 13.19	24.80 x 20.47	35.43 x 27.56	39 x 35
Max. Speed (Pieces/min)	45	40	35	25
Max. Film Width (in)	22	28	38	37
Conveyor Speed (ft / min)	0 ~ 60	0 ~ 60	0 ~ 60	0 ~ 60
Power (Volt./ Ph./Amps/ Kw)	220 / 1 / 13 / 2.5	220 / 1 / 15 / 3	220 / 1 / 20 / 4	220 / 1 / 18.5 / 4
Air Pressure/ Cons. (PSI / CFM)	60 / 2.5	60 / 3	60 / 3	90 / 3
Machine Dimensions (in)	59 x 54 x 48	79 x 60 x 52	96 x 72 x 52	107 x 72 x 52









Automatic Vertical L-Bar Sealing Machines



Model	801	
Product Size LxWxH (in)	(2 ~ 15.75) x (2 ~ 11) x (0.1 ~ 6)	
Sealing Blade Size (LxW) (in)	17.72 x 13.19	
Max. Speed (Pieces/min)	45	
Max. Film Width (in)	22	
Conveyor Speed (ft / min)	0 ~ 60	
Power (Volt./ Ph./Amps/ Kw)	220 / 1 / 13 / 2.5	
Air Pressure/ Cons. (PSI / CFM)	60 / 2.5	
Machine Dimensions (in)	59 x 54 x 48	

