

Paste Viscosity Packing Machine DXDL-240



Description

1. Can finish the function of bag making, measuring, filling, sealing, cutting and counting.
2. Controlled by computer and step motor pull bag, flexible bag length cutting, operator needn't to adjust the unloading working, saving time and saving films.
3. Separate PID control to temperature, suitable for various packing materials.
4. Option device: ribbon printer, filling device, gas-exhaust device, horizontal sealing punching device, rotary cutter, small cutter, former beat device, batch pneumatic cutter.
5. Simple driven system, working more stable and easy to maintain.
6. Packing material: (PET/PE), (Paper/PE), (PET/AL/PE), (OPP/PE)
7. The machine is with programmable controller as well as an English display screen that makes it easy to operate and convenient.
8. Photoelectric digital tracking system makes it possible to set the length of package and when packing film with cursor mark is used, and the machine will be automatic stopped if it cannot track the mark after three bags.

Parameter Date

Model	DXDL-240
Packing speed	40-60bag/min
Range of measurement	0 -100ml
Bag size	W:30-120mm L:30-120mm
	Bag size can be lengthened according to customer requirement
Voltage	380V or 220V or made accordingly
Power	1100W
Dimension	1150*750*1750mm
Packing material	(PET/PE), (Paper/PE), (PET/AL/PE), (OPP/PE)
Method of Measurement	Piston pump type
Weight	280kg