



GF-400L/F automatic filling and sealing machine



This product is the first company to introduce foreign conduct, combined with the GMP requirements successfully developed to optimize the design of high-tech equipment. With a reasonable structure, function Chiho, easy operation, accurate loading capacity, smooth operation, low noise characteristics. PLC programmable controller to make the machine run procedures, filling and sealing to play yards Lot (including production date) and other processes from liquid to highly viscous fluid materials (paste) automatic job. The tubes, plastic tubes, ideal for composite tube filling and sealing of cosmetic, pharmaceutical, food, adhesives and other industries, in line with the requirements of GMP.

Main features:

- 1) High quality LCD programmable controller and buttons combine operations screen, fully grasp the device steeples device parameters, yield counting statistics, pressure indication, fault display and other operating conditions, make the operation simple and humane.
- 2) Automatic completion of people for pipe, benchmarking, table filled with inert body temperature (optional), filling, sealing, play yards, finished the export process.
- 3) Accuracy of the standard system, reducing the tube and color-coded color range.
- 4) External adjustment parts, the position digital display, adjust fast, accurate (for multi-standard, multi-species production).
- 5) Machine, light, electricity, gas integration, real column ductless no filling, for tube in place, low pressure, automatic display (alarm); when you open the protective door can automatically shut down, such as automatic functions.

The main technical parameters:

Model	GF-400L	GF-400F
Hose Material	Metal pipes, tubes	Plastic pipe, composite pipe
Hose diameter	Φ10- Φ50	Φ10- Φ50
Hose length	50-250 (Customizable)	50-300 (Customizable)
Filling capacity	5-500ml / branch (adjustable)	5-800ml/branch (adjustable)
Filling accuracy	≤±1%	≤±1%
Speed(r/min)	3-10	2.5-7
Production capacity (pcs / min)	30-60	30-60
Compressed air	0.55-0.65mpa	0.55-0.65mpa
Motor Power	2kw(380V/ 220V 50Hz)	2kw(380V/ 220V 50Hz)
Sealing power	3kw	3kw
Dimensions (mm)	2620×1020 ×1980	2620×1020×1980
Weight (kg)	1100	1100