

Automatic Irregular Shape Sachet Multi Lanes Cosmetic Packing Machine HY-IY420



Suitable for automatic packaging of liquid paste products in cosmetics, food, health care, pharmaceutical industry, such as: cleanser, skin cream, mask mud, repair cream, essence milk, liquid, lotion, shampoo, conditioner, hair mask, fog eyebrow milk, etc.; chili sauce, soy sauce, mustard sauce, salad dressing, tomato sauce, etc.; energy drink, energy jelly, energy supplement, etc.; syrup, red ginseng drink, antibacterial cream, dampness Cream, acne cream, etc.

Features:

1. Adopt high configuration: Siemens PLC controller and color touch screen operation; Taiwan AIRTAC cylinder; France Schneider switching power supply, etc.
2. Full pneumatic control including filling and bag making, simple operation, less wear parts in the later period, reducing parts replacement.
3. Material: The contact part of the box and material is made of SUS304, which meets the requirements of GMP production.
4. The heat-generating parts and moving parts are hidden in the protective cover, and the electric cabinets are wired and strictly in accordance with electrical standards.
5. The equipment is equipped with casters for easy handling and movement.

Characteristics:

1. Suitable for 1-20ml emulsion cream or water-based product trial packaging.
2. This host can be customized to one out of three, or you can customize one out of four (single or even).
3. The die cutting die is formed once, the cut is flat, no wrong side, no burrs.
4. Punching die adopts HKS-9 material, after six processing techniques, high durability and long service life.

5. This equipment is complicated to operate, requires professional technical operators, or arrange special personnel to come to our company for 3-5 days of professional training.

Specification:

Model	HY-IY420
Filling Range	1-20ml/10-30ml
Lanes	1/2/3/4
Sachet Size	W: 25-90mm, L: 30-170mm
Max. Film Width	420mm
Sachet Type	Irregular shape sachet
Filling Method	Pneumatic pump/magnetic pump
Capacity	80-100 PPM
Power Voltage and Consumption	220V50-60HZ/4.5KW
Air Pressure and Consumption	0.6m ³ /min 0.6-0.8Mpa
Dimension (L*W*H)	1500*1400*2155mm
Weight	550KG
Packaging Film Materials	PE laminated film, such as PET/AL/PE, PET/PE, Nylon/PE, etc.
	Thickness: 0.08~0.12mm(3 or 4 layers)
	Inner Core Diameter: 75mm
	Outer Roll Diameter: 300mm-500mm