

ATM-320L Autompack Shampoo Liquid Sachet Filling Sealing Packing Machine



AUTOMPACK's mission is to keep developing intelligent vertical packaging machines and offer full automatic packaging solutions. till nowadays, we already have successfully developed over 25types packaging machine included in pillow bag/gusset bag/quad seal bag/3 or 4 sides sealing bag, connected strip bag form fill seal bagger, a these equipment able to pack all different kinds of material such as most daily snacks, food, liquid, paste, Powder etc. forming and metal spares, high technical material, vegetable, etc. cover agriculture, industrial, manufacturing all sorts fields material and commodities to pack favorable through our vertical packing machine.

Technical Characteristics:

- It is controlled by a micro-computer, with touching the screen, and the operation is simple .
- PLC computer system, function is more stable, adjust it with any parameters, and don't need to stop machine.
- It can stock ten dispose, simple to change variety.
- Temperature independent control system, precision degree get to $\pm 1^{\circ}\text{C}$.
- Horizontal, vertical temperature control, suitable for various of mix composite film.
- Bag-making, sealing, packing, print date in one operation.
- Work circumstance quiet, low noise.
- High precision structure for simple and easy operation and repair.
- It's owns simple circuitry and outstanding function.
- Optional device: Linked-bags device, hole punching device, pneumatic type end sealing for good performance.

Application:

Suitable for packing for all kinds of liquid material which such as liquid milk, water, honey, juice, tomato paste, ketchup, sauce, oil, etc. Various bag types are available, e.g. back-sealing bag, 3 sides seal bag, 4 sides seal bag, stick bag, linking bags, etc.

➤Measuring range: 100---500ml (By changing liquid pump).

Technical Parameters:

Model	ATM-320L
Packing speed (bags/min)	15-80bags/min
Max width of packing film (mm)	80mm-320mm
Packing pouch size(mm)	(L): 50-200mm (W): 30-150mm
Total power (kw)	2.2kw
Filling range(ml)	2-500ml
Max outside diameter of rolling film (mm)	≤φ300
Packing film thickness(mm)	0.05-0.10
Gross weight(kg)	350kg
Machine dimension(mm)	(L)970×(W)680×(H)1950mm
Working voltage	220v 50hz
Packing material applications	OPP, PE, PVC, OPP/OPP, OPP/PE, PET/VMPET/PE