



GS-WZP Full Line Auto 10-14 Heads Weighing Packaging with Z Type Conveyor



It's suitable to use in packing the high accuracy and easy fragile material, such as : puffy food, crispy rice, Potato Chips, Snacks, candy, pistachio, sugar, apple slices, dumpling, chocolate, pet food, small wares etc.

Technical Parameters:

Model	GS-WZP320	GS-WZP420
Packing speed	5-60 bag/min	5-60 bag/min
Bag size	(L)50-250mm (W)60-150mm	(L)50-350mm (W)100-200mm
Bag making mode	Pillow-type bag, standing bag, punch bag	Pillow-type bag, standing bag, punch bag
Range of measuring	150-750ml	150-1000ml
The maximum width of packing film	320mm	420
Thickness of film	0.04-0.08mm	0.04-0.08mm
Air consumption	200L/min	200L/min
	0.7×105Pa	0.7×105Pa
Main power/voltage	2.2KW/220V 50-60Hz	2.2KW/220V 50-60Hz
Dimension	L1400×	L1400×
	W970×H1600mm	W970×H1600mm
The weight of switchboard	400kg	450

Model	GS-WZP520	GS-WZP620
Packing speed	5-60 bag/min	5-50 bag/min
Bag size	(L)50-350mm (W)150-250mm	(L)150-400mm (W)150-300mm
Bag making mode	Pillow-type bag, standing bag, punch bag	Pillow-type bag, standing bag, punch bag
Range of measuring	150-1500ml	300-2000ml
The maximum width of packing film	520	620
Thickness of film	0.04-0.08mm	0.04-0.08mm
Air consumption	200L/min	200L/min 0.7×105Pa
	0.7×105Pa	
Main power/voltage	2.8KW/220V 50-60Hz	3.2KW/220V 50-60Hz
Dimension	L1600XW	
	1400XH2000mm	
The weight of switchboard	500	800

Model	GS-WZP720
Packing speed	5-50 bag/min
Bag size	(L)250-450mm (W)200-350mm
Bag making mode	Pillow-type bag, standing bag, punch bag
Range of measuring	300-3000ml
The maximum width of packing film	720
Thickness of film	0.04-0.08mm
Air consumption	200L/min 0.7×105Pa
Main power/voltage	3.7KW/220V 50-60Hz
Dimension	
The weight of switchboard	1000