

TODAY MACHINE

Simple & Responsible Since 2001

Flow ability Liquid Stick Packaging Machine VFFS-280LS



Juice, Water, Jelly, Ice pop, ice lolly...

Standard:

- Closed sealer housing
- Intuitive operator guidance on the button/touch panel
- Integration of all identification systems
- Printed mark identification & measurement of bag lengths
- Use of different heat sealing and welding instruments
- Minimal time required when changing rolls
- Stop when film roll end. Detect the fault automatically.
- Seal tight, no leaking.

Available option:

- Stainless steel and Paint version
- Display panel: Touch screen and Button screen
- Date & batch printer
- Date embossing system
- Easy tearing notch
- Round and euro-hole punch, carrying handle punch
- Mixing system
- Keep warm hopper system
- Numerical control cutter, 1-99 packet
- Flat bottom package with center seal
- Frequency control system, less noise
- Power supply: – 110V, 120V, 220V, 240V. – 50Hz, 60Hz.

Technical parameter:

Model	VFFS-280LS	VFFS-280LS+
Film width	Max 100mm,11”	Max 300mm,11”
Bag size	L: 40-275/295mm,2-11”	L: 40-275/295mm,2-11”
	W: 10-30mm,0.4-1.5”	W: 10-145mm,0.4-5”
Output	40-80 pcs/min	30-50 pcs/min
Bag type	Pillow seal	Pillow seal
Packing range	Gravity with Level Control	Suction Pipe with Volume Control
	10-200ml	5-45ml, 20-100ml, 50-280ml, 100-550ml
Power	1.2KW	2KW
Dimension	1100*900*1900mm	1100*900*1900mm
(L*W*H)		
Weight	320kg	350kg