

## Liquid Paste Packing Machine XY8-300-J/Y



Rotary liquid paste pouch packing machine line mainly installs rotary packing machine and liquid/thick-liquid filling machine, suitable for packing all kinds of liquid and thick-liquid (sauce), such as fruit juice, tomato sauce, seasoning sauce, chili sauce, peanut butter, hand sanitizer, liquid detergent and so on.

It has wide range of packaging, by selecting different survey meter, can be applied to the liquid particle powder paste irregular shape product.

### **Premade pouch**

Rotary liquid paste pouch packing machine line is suitable for all kinds of compound bags, such as flat bag, 3-side sealing bag, 4-side sealing bag, zipper bag, standup bag etc.

Main Features for the rotary pouch packing machine:

1. High quality and performance, the frame is made of 150mm thickness 304# stainless steel.
2. Good stable and also good machine exterior, own extensive range in filling productions  
Easy operate by touch-sensitive screen (Weinview, Taiwan), PLC (OMRON, Japan) and electric control system
3. Friendly man-machine interface
4. Speed can be adjusted by frequency conversion within the range.
5. Perfect sealing system, Good safety secure and so on
6. No bag—no filling-no sealing, machine alarm Bag opening miss- no filling-no sealing, machine alarm
7. Machine stop or alarm when the air pressure is abnormal
8. Error position display at the control panel. Control panel locate on the right side top of the machine

9. Outside of the machine and all the parts which touch production all made by stainless steel.
10. There are several safety doors made by aluminum Profile Frame. The doors are equipped with safety proximity sensors
11. Machine surface can be washed by water and brushed by cloth

**Parameters:**

| <b>Model No.</b>  | <b>XY8-300-J/Y</b>   |
|-------------------|--|
| Bag Type          | Flat bag, 3 sides sealing, 4 sides sealing, Zipper bag, Doypack etc. |
| Packing Material  | Composite film, PP etc.  |
| Bag Size          | W:100-300mm L:150-400mm  |
| Weight Scope      | 50-2500g   |
| Packing Speed     | 15-30 bags/min (speed is decided by material and its filling weight) |
| Packing Accuracy  | $\leq \pm 1\%$   |
| Voltage           | 3.38KW, AC380V, 50HZ   |
| Machine Dimension | 3400X2000X1780mm   |