

KL-450X Down-Paper Pillow Packing Machine



Main performance and structure features

1. Double transducer control, flexible bag length cutting, operator needn't to adjust the unloading working, saving time and saving films.

- 2. human-machine operation, convenient and quick parameter setting.
- 3. Self diagnosis failure function, clear failure display.

4. High sensitivity optical electric color mark tracking AND digital input cut position which makes the sealing and cutting more accurate.

- 5. Separate PID control to temperature, suitable for various packing materials.
- 6. Stopping the machine in selected position, no sticking to the knife and no waste packing film.
- 7. Simple driving system, reliable working, convenient maintenance.
- 8. All the controls are achieved by software, convenient for function adjusting and upgrading.

Application

Suitable for packaging soft, strip and unorganized objects like towels, tissues, noodles, egg rolls, sausages, fish, ice-lollipop, soft candies, biscuits, fresh fruits, etc.

Specification

| Туре | KL-450X |
|-----------------|-----------------------------|
| Film width | Max. 450mm |
| Bag length | 120-450mm |
| Bag width | 50-210mm |
| Product height | Max.60mm |
| Film roll | Max. 320mm |
| Packaging rate | 40-230 bag/min |
| Power | 220V,50/60HZ,2.8KVA |
| Machine size | (L)4020X(W)820X(H)1320mm |
| Machine quality | 750kg |
| Remarks | Optional Air filling device |