

Multi Lines VFFS Packing Machine DB300/DB450/DB600/DB800



Applicable bag type: a variety of stick pack, standard pillow bag or irregular bag, four sides sealed bag.

Applicable film materials: Avariety of laminated films, aluminum film, paper film, film thickness range 0.07mm~0.1mm.

Applicable packing materials: All kinds of fine powder, small granule, liquid and gel, such as coffee powder, spice powder, milk powder, sugar, salt, pepper, honey liquid, oil liquid, shampoo, ketchup, etc.

Feature:

- PLC control, man machine interface, easy to operate and maintain.
- Equipped with servo motor and optical tracking devices to keep high accuracy.
- The frame of machine is made of stainless steel #304. equiped with auto-stop protection function when open the door.

Parameter:

Item No.	DB300	DB450
Packing Lines	2~6 lines	3~8 lines
Film Width	90~300mm	300~450mm
	L: 60~18mm	L: 60~180mm
Bag Size Range		
	W: 17~60mm	W: 17~60mm
Each Line		
	25~45bags/min	25~45bags/min
Packing Speed		
Gas Pression	0.6MPa	0.6MPa
Gas Consumption	0.5m³/min	0.6m³/min
Power Requirement	6KW/220V/50(60)Hz	7.5KW/220V/50(60)Hz
Machine Size(mm)	L*W*H=1300*1900*1750	L*W*H=1500*1900*1750
Machine Weight	680KG	600KG

Item No.	DB600	DB800
Packing Lines	4~10 lines	5~10 lines
Film Width	450~600mm	600~800mm
	L: 60~180mm	L: 60~180mm
Bag Size Range		
	W: 17~60mm	W: 17~60mm
Each Line		
	25~45bags/min	25~45bags/min
Packing Speed		
Gas Pression	0.6MPa	0.6MPa
Gas Consumption	0.9m³/min	1 m³/min
Power Requirement	10.5KW/220V/50(60)Hz	11KW/220V/50(60)Hz
Machine Size(mm)	L*W*H=1650*1900*1750	L*W*H=1850*1900*1750
Machine Weight	700KG	800KG