

5 Gallon Water Filling Machine CGZ12-12-6



Introduction of Water Production Line:

- 1. The whole machine adopts the design of stuck bottleneck suspension operation mode so that the bottle is stable and reliable under high-speed operation, and at the same time, the number of changed parts is greatly reduced, making it more convenient and fast when changing the bottle type.
- 2. A new generation of stainless steel flip bottle clamp is adopted so that the clamp does not contact the upper part of the thread of the bottle mouth, and a spray head is provided so that the inner wall of the bottle can be rinsed fully without dead corners.
- 3. Adopting advanced gravity filling principle, the filling is fast, stable, and accurate.
- 4. Adopt magnetic torque type capping head to realize capping and capping. The capping torque is infinitely adjustable, the sealing is tight and reliable, and the cap is not hurt.
- 5. The whole machine adopts man-machine interface touch screen buttons, PLC computer control, and is equipped with a cover missing and overload protection alarm device, which can find and eliminate faults in time and have a high degree of production automation.
- 6. The parts in contact with water are made of high-quality stainless steel, and the main electrical components are all products of well-known international manufacturers.

Main Features:

- 1. Rinsing system: Combined with rotary tray with clamp, water distributing tray, water tank and rinsing pump.
- 2. Filling system: Combined with hydraulic, filling valve, controlling ring, and elevator-cylinder.
- 3. Capping system: Combined with capper, cap sorter and cap falling track.
- 4. Driving system: Combined with main motor and gears.
- 5. Bottle transmitting system: Combined with air conveyor, steel star wheels and neck supporting carrier plates.
- 6. Electrical controlling system: this part is frequency inverted, PLC controlled and touch screen operated.

Technical Parameters:

Model	CGZ12-12-6	CGZ18-18-6	CGZ24-24-8	CGF32-32-8
Capacity	4000BPH	8000BPH	12000BPH	15000BPH
Applicable bottle type	Bottle diameter:50-100mm; height:150-320mm; Volume:330-1500ml			
Applicable bottle shape	Plastic Screw cap			
Gas pressure	0.6	0.6	0.6	0.6
Motor power	3.1	3.5	3.8	3.8
Machine size	2.45*1.65*2.1m	2.6*1.8*2.1m	3*2.2*2.4m	4*2.2*2.4m
Weight	2000kg	2500kg	4200kg	4800kg