

Rotary Premade Pouch Bagging TOPY-200B



For powder filling, TOP Y MACHINERY provides auger filler machine, this type can do measuring and filling work. Due to the special professional design, it is suitable for the fluidic or low-fluidity materials, like milk powder.

Function and Characteristics

- 1. Automatic checking: no pouch or pouch open error, no fill, no seal. The bag can be used again, avoid wasting packing materials and raw materials.
- 2. Safty device: Machine stop at abnormal air pressure, heater disconnection alarm.
- 3. Horizontal conveyer style to giving bag: it can put on more bags on the bag storage and have a low requirement about the quality of bags.
- 4. The width of the bags could be adjusted by electrical motor. Press the control-button could adjust the width of clips, easily operate, and save time.
- 5. It matches with the glass safty door. The machine will stop working when you open the door. So that it could protect the safty of operators. At the same time, it could prevent dust.
- 6. The opening zipper framework is special in the feature of zipper bag, it can avoid distortion or destroy when open the zipper.

Parameter

Model No.	TOPY -200B
Working Position	Eight-working position
Pouch material	Laminated film, Single PE, PP
Pouch pattern	Zipper & Stand-up pouch
Pouch size	W:100-210mm L:100-350mm
Filling Scope	10-1000g
Weight Accuracy	±0.1-2g
Speed	10-50 pouches/min (The speed depends on the product status and flling weight)
Voltage	380V 3phase 50HZ/60HZ
Total power	6.5KW
Compress air	0.6m3/min(supply by user)