

## *KENO-W102 Automatic Wrapping Machinery*



Turn on the power; Choose job mode on the screen controller (Manual or Auto); Pull out suitable film, twist onto the unwinding object; Push button 5 to start the turntable; Push button 9 to rise or 3 to drop (option)(Manual); Push button 0 to start; (Auto); Cut the film when wrapping finish

### **Characteristic and strong point:**

- Adopting programmable control (PLC) and screen controller
- Equipped with a photoelectric detector, automatically testing the goods height and controlling the travel limit.
- Rotary table can reset automatically
- Pre-stretch unit
- Soft start/Soft stop
- It is available for wrapping light products.

### **Technical Parameters**

- Electricity: AC220V, 1phase/ 380V, 3phase, 50Hz
- Power: 1.25KW
- Machine dimensions: Turn table DIA.  $\Phi 1500$ : 2340X1500XH 2400(max 3000)turn table DIA.  $\Phi 1650$ : 2629X1650XH 2400 (max 3000)turn table DIA.  $\Phi 2000$ : 2840X2000XH 2400 (max 3000)
- Turntable thickness: 85mm
- Speed of turntable: 0-12 r/min
- Capacity: 2000kg
- Percent of pre-stretch: 250%
- Machine weight: 700kg
- Gross weight: 800kg
- Machine color: Blue/Yellow or Gray/Blue (Custom-made color is available)