

YS-BS-2520-IP Vertical Packaging Machine



- Intermittent pull film movement, Simple structure, Economical and practical
- Continuous motion leads to high productivity
- Lean machine concept enables cost-effective production
- Maintenance-free servo-technology ensures reliable production
- PLC controls enable precise machine movements for smooth production and good bag quality
- Intuitive HMI allows easy operation and short training time
- Open machine concept for easy access and maintenance
- Compact machine design for good ergonomics, product-conserving filling and saving space

Technical Parameters

Model	YS-BS-2520-IP-A	YS-BS-2520-IP-P	YS-BS-2520-IP-GB
Bag type	1 .Pillow bag	Only pillow bag	Gusseted bag+
	2. Gusseted bag		bottom block
Standard capacity	10-100 bags/min	10-100 bags/min	10-100 bags/min
Size of pillow bag	Width : 60-250mm	Width : 60-250mm	Width : 60-250mm
Max size: 4.5L	Length: 60-400mm	Length: 60-400mm	Length: 60-400mm
Size of Gusseted bag	Width : 50-220mm		Width : 50-220mm
Width>2 times side depth	Depth : 35-110mm		Depth : 35-110mm
	Length: 60-400mm		Length: 60-400mm
Film parameter	packaging material:OPP/AL/PE, PET/VMPET etc.		
	Film diameter: ≤600mm		
	Core diameter:76mm		
Total power	5 KW		
Air pressure	≥0.5MPa		
Air consumption	HS closure, 0.32NL/cycle		

Outer dimensions (appr.)	1800*1270*1615mm
Weight (appr.)	680kg
Power supply (optional)	3N-PN-50Hz 380V/220V (3P 5 wires)