

DQL5545PEG High Speed Automatic PE film L bar type Sealer Sealing Packaging Machine



1. The sealing knife adopts copper alloy sprayed with Teflon, it won't stick film, sealing fastness, without smoke, non-pollution. Horizontal and vertical sealing knife adopt whole connecting without gap, the film won't break. Sealing frame adopts high quality alloy steel, the sealing quality is stable, frame difficult to be damaged.
2. The machine has entire automatic system, it equipped with sensors can reach high speed automatic working.
3. It is convenient to adjust according to different sizes products, just adjust the handle wheel can reach it, operation is easy.
4. It can be connected with production
5. It has protection function to avoid sealing product wrong and ensure the safety of operator

Application:

This machine is widely used in foodstuff, drinks, printing, pharmaceutical, floor, hardware, shoebox and other Electric business products. It is suit for PE packaging material.

Technical Parameters

Model	DQL5545PEG
Max packing size(mm)	L+2H≤550, W+2H≤450, H≤130
Max sealing size(mm)	L550×W450
Power(KW)	2.2
Capacity	0-30 pcs/min
Voltage	220V 50/60HZ
Sealing temperature	180°C-250°C depends on thickness of film and environment temperature
Air pressure(Kg/cm2))	5-6
Packing material	PE
Machine weight(kg)	320
Machine size(mm)	L1760×W940×H1580