

YS-MG series Rapid Mixer Granulator (RMG)



Super mixer granulator, also called Rapid mixer granulator RMG, is suitable for the high speed dispersion of dry powders, aqueous or solvent granulations. Rapid mixer granulator provides perfect mixing in short time for wet granulation process. In high shear granulation, dry powder is mixed in a bowl using impeller that spins powder into a vortex.

Function

Mixing: powder and powder.

• Granulation : powder and binder solution.

Theory

Inside the cone-shaped vessel, the main impeller mix the powder into fluidized vortex and form lumps with the cinder solution. then the high speed chopper cut the lumps into even granules by high speed action.

Application

- o Bio-tech / Pharmaceutical: powder mixing and granulating before tabletting.
- o Chinese Medicine: powder and soakage plaster mixing.
- o Food: seasoning mixing and granulating.
- o Chemical:
 - Chemical material mixing and granulating.
 - Electronic metal powder mixing and granulating.
 - Plastic powder mixing and granulating.

Feature

- High uniformity, very different proportion also can uniformly mixing.
- Short mixing time, about 5 ~ 10 min/batch finished.
- Good tightness, use air bag to clamp the cover.
- Multi safety interlock device, high safety.
- Optional equipment for different product feature.
- Multi functions of mixing, granulating and drying can produce hormone or anti-cancer medicine.
- All the design and manufacture are qualified cGMP standard and FDA requirement.

Specification

Model	Full Volume(L)	Work Volume(L)	Capacity:Kgs/Batch	Size(W x L x H) (MM)
YS-MG-1	1	0.4-0.8	0.2-0.4	310x560x753
YS-MG-5	5	2-4	1-2	350x600x800
YS-MG-20	20	8-16	4-8	500x1360x1210
YS-MG-100	100	40-80	20-40	700x1600x1350
YS-MG-150	150	60-120	30-60	850x1900x2100
YS-MG-250	250	100-200	50-100	900x2400x2500
YS-MG-300	300	120-240	60-120	2800x2900x3000
YS-MG-400	400	160-320	80-160	2900x3100x3500
YS-MG-600	600	240-480	120-240	3000x3300x3900
YS-MG-800	800	320-640	160-320	3100x3500x4000
YS-MG-1000	1000	400-800	200-400	3200x3800x4100
YS-MG-1200	1200	480-960	240-480	3300x4000x4300