

## *TY-137 Wrap*



TY-136 (Servo) & TY-137 (Cylinder) middle speed sleeve sealing machine (not including shrink tunnel) is suitable for products in one tray pack, single carton or some simple collections of large products. Available with transparent PE shrink film (each Top and Bottom film cradle) OR printed PE film (only Top film cradle) Its speed could up to 35 packs per minute depends on the product dimensions.

### **Features**

- Machine constructions: use S-41 steel materials.
- Frames formed up by model.
- Specified spare parts kit.
- HMI control allows for easy change of machine speed and reciprocation.
- Safety device for cutting blade: a micro-sensor combined with automatic blade return provides safety protection in cut a hard object.
- Employs constant temperature one-piece fabricated bronze sealing blade. Draw-out type constant temperature heater combined with SSR constant temperature control features maximum stability of temperature, power saving and easy replacement.
- The sealing modes including seal type and reciprocating type.
- Sealing device: heating sealing knife, equipped with picked-up type heating tube & SSR temperature control.
- Double-rod film holders: fitted with micro-sensing film drive motor
- Film in roll replaced easily.
- CE model available.

## Specification

Model	Machine Size (L x W)	Consumption	PACKAGE RANGE (LxWxH mm)	SPEED RANGE	VOLTAGE
<b>TY-136 (servo)</b>	2950 x 1900 mm	10kw	as specified	1~35 PPM	220V/380V/415V
<b>TY-137 (cylinder)</b>	2850 x 1450mm	10kw	as specified	1~35 PPM	220V/380V/415V

\* Production capacity is subject to product size, type of product, shrink film material and shrink film thickness.

\*\* Specifications are subject to change without prior notice.

## Applications

Suitable for products in one tray pack, single carton or some simple collections of large products.