

GSZP Series High Speed Tablet Press Machine



1. Made of stainless steel, the housing is fully closed. The surface of the rotary turret is covered with a hardened layer so that the turret surface is wear resistant. The machine conforms to GMP requirements.

2. High speed with large quantity punches, double press rollers, suitable for mass production.

3. Double impeller type force feeder, improve granules flow-ability and filling performance, ensure the filling precision.

4. Perfect tableting system, twice compression forming, reasonable framework with proper space and big pressure roller, machine performance is reliable and no tablet weight difference.

5. Automatic oil grease central lubrication system, ensure the lubrication of pressure rollers.

6. The machine can stop automatically in case of over pressure to protect the punch pins from being damaged.

7. With voltage overload, over current protection devices.

8. PLC and touch screen control, automatic and easy control.

Model	GSZP35	GSZP37
NO.of stations	35	37
Type of Tooling	IPT	IPT
Max.Pressure(KN)	80	80
Max.Pre-pressure(KN)	60	60
Max.Filling Depth(mm)	18	18
Max.Tablet Dia(mm)	25	23
Output Capacity(pcs/h)	190	200
Max.Turret Speed(r/min)	45	45
Machine Floor Space (mm)	1170*1290*1900	1170*1290*1900
Main Net Weight(kg)	3500	3500

TECHNICAL PARAMETER