

Rotary Tablet Press Machine KTMD-series



Feature:

- The press can be configured with one or 2 output chutes. Conventional tablets can be manufactured with double sided pre and main compression for highest outputs, or for double layer tablets by single tablet output. The changeover process is easily possible by the user with the most basic of training.
- Quiet running through precise rail and turn table.
- Low vibration by strength design of a frame.
- The convenient operation panel. The functional switches and signals are integrated in 12" touch screen to make it possible that machine is convenient operated.
- The cover of the upper punch and the dust-collecting duct protect the machine from dust and prevent alien substances from adulterating

Specifications:

| Model | KT41MD | KT49MD | KT59MD |
|--------------------------|-------------------|-------------------|-------------------|
| Number of Station | 41 | 49 | 59 |
| Dia tablet speed (r.p.m) | 10-60 | 10-70 | 10-70 |
| Tablets/hr | 49 200-295 200 | 58 800-411 600 | 70 800-495 600 |
| Type of tooling | EU-D | EU-B | EU-BB |
| Max. table dia.(mm) | 25 | 16 | 13 |
| Max. pressure dia.(ton) | Pre 10 / Main 10 | Pre 10 / Main 10 | Pre 10 / Main 10 |
| Max. filling depth (mm) | 18 | 18 | 18 |
| Main motor(kw) | 11 | 11 | 11 |
| Dimension (W x D x H mm) | 1,200×1,250×1,816 | 1,200×1,250×1,816 | 1,200×1,250×1,816 |
| Weight (kg) | 4,5 | 4,5 | 4,5 |