



DPP-140 Blister Packing Machine



1. Adopt the high-power transmission of the domestic latest model, and spread to move the stalk from the row chain to remove other gear transmission error and noise.
2. Imports of used electrical control systems, customers can request configuration shut fill leakage detection and missing tablets removed devices (Omron sensors). Used imports Frequency Converter.
3. Unit stages portfolio : PVC shape, feed, heat sealing as a tropical aluminum cold forming, heat sealing, Punching a section of the body for hours packaging.
4. Photoelectric control systems, PVC, PTP, tropical aluminum packaging automatic feed, scrap automatic admission Device, to ensure the long-synchronous multi-position stability.
5. Additionally photoelectric detector may calibration device, service imports stepper motor drive, the transmission version printing and packaging, optimize packaging grades.
6. The machine applies: capsules, tablets, sugar-coated, capsules, injections, and other special-shaped medical device, light industry and food, electronic components sealed blister packaging.

Technical Parameters

Model	DPP-140
Cutting Frequency	5-30 (Times/min)
Production Capacity	3600 Edition / time
Max. Forming Area And Depth (mm)	140*100*26 (mm)
Travel Range (mm)	20-120 (Standard Depth 14mm)
Standard Plate (mm)	80*57mm (Can be manufactured as user's requirements)
Air Pressure (Mpa)	0.6-0.8
Air Supply	≥0.2m ³ /min
Total Power	380V/220V 50Hz 3.2Kw
Main Motor Power (KW)	0.75Kw
PVC Hard Pieces (mm)	0.15-0.5*140 (mm)
PTP Aluminum Foil (mm)	0.02-0.035*140 (mm)
Dialysis Paper (mm)	50-100g*140 (mm)
Mould Cooling	Tap Water Or Circulating Water
Overall Dimensions (mm)	2300×560×1410(L×W×H)
Weight (kg)	800(Kg)
Noise target	<75dBA