

ZP-35 Rotary Tablet Press



The machine is used to press all sorts of granular materials, like geometry shape of profiled sheet, double lettering piece, traditional Chinese medicine tablet, western medicine tablet, calcium tablet, buccal tablet, spirulina tablet, milk tablet, candy tablet, effervescent tablets, chewable tablets, seasoning block, chicken pieces, camphor ball (naphthalene), aromatic piece, disinfection tablet, fertilizer tablet, pesticide tablet, button cell, electronics, metallurgy powder ceramic grain, etc

The structure has double pressure, two sets of roller, frequency control of motor speed, depth of fill, tablet thickness are can adjusted.

The machine is equipped with mechanical buffer device, the pressure overload can automatically shutdown, killing all had a broken impact protection, can avoid parts damaged.

In accordance with GMP.

According to user's requirements, the machine can be equipped with a vacuum cleaner, screen machine, feeding machine, etc.

Technical Parameters

Product model	ZP-35
Quantity of punch&die(Set)	35
Max. Pressure (KN)	80
Max. Dia. of Tablet (Milimetre)	13
Max. Thickness of Tablet (Milimetre)	6
Max. Depth of Filling (Milimetre)	15
Rotate speed (r/min)	3-35
Production Capacity (pc/h)	147500
Electric power source(V/Hz)	380/50
Power (KW)	4
Outside measurement (Milimetre)	1240*980*1650
Weight (Kilogram)	2000