

Automatic Liquid Pouch Packing Machine XY8-210-J/Y



Suits to pack all kinds of milk, soymilk, soy sauce, ketchup, water, juice, chili sauce, detergent liquid, cream, shampoo, oil, jam yoghurt etc.

Kinds of preformed pouches: Stand up pouches, doypack with zipper, 3 sideseal bags, 4 side seal bags, flat bags, pouch with hole, spout pouch etc

Rotary pouch packing machine main advantages:

- 1. It uses stainless steel 304 shell for food grade required.
- 2. Automatic detection. No pouch or pouch is not opened completely, no filling, no sealing.
- 3. Horizontal Infeed conveyor suits for bags with zipper, max. put 300pcs each time.
- 4. Zipper Openner System: Servo motor (Yaskawa / Japan) controlled.
- 5. Independent temperature control system (Omron/Japan).
- 6. PLC adjust bag width clamping: Only needs 2mins by auto PLC for adjust different bag width sizes.
- 7. Automatic lubrication system: PLC control the lubrication time, automatically lubricate the machine parts instead of by manual.
- 8. It includes ribbon type date code: 3 lines * 17 characters.
- 9. Guarding: Glass Door Alarm / Air Pressure Abnormal
- 10. Internal grooved cam design: The technology with high precision, suits for max. packing speed: 50 cycles/min with stable running.
- 11. Use free oil vacuum pump, avoid polluting the environment in the production.

Parameters:

| Model No. | XY8-210-J/Y |
|-------------------|--|
| Bag Type | Flat bag, 3 sides sealing, 4 sides sealing, Zipper bag, Doypack etc. |
| Packing Material | Composite film, PP etc. |
| Bag Size | W:100-210mm L:150-300mm |
| Weight Scope | 5-1500g |
| Packing Speed | 15-40 bags/min (speed is decided by material and its filling weight) |
| Packing Accuracy | ≤±1% |
| Voltage | 2.6KW,AC380V,50HZ |
| Machine Dimension | 3100X1800X1450mm |