

Automatic Cream Bottle Jar Capping Machine APM



This automatic capping machine suit for the bottle is conveyed in a straight line and then capping. Suitable for Plastic/Glass covers of different sizes and shapes, duckbill caps, spray gun caps, straw type pump caps, etc. Widely used in Cosmetic, food, beverage, daily chemical, pharmaceutical and other industries.

Main Features:

- ★ Wide range of application, electrical control movement, positioning device, easy operation, all kinds of bottle caps can be used, with the bottle cap guide mechanism, can ensure the consistency of the direction of the pump head.
- ★ Convenient adjustment, quick conversion bottle.
- ★ Easy to operate, better screw capping effect.
- ★ The operator can tighten the cap without damaging the cap by adjusting the torque, rotational speed and time of the cap according to the material, style and tightness requirements of the bottle cap.
- ★ Beautiful and decent appearance, which adopts special polishing technology so that it is shining like a mirror, displaying luxurious character.
- ★ This machine universal, suitable for bottles, bottle caps of a wide range of manufacturers to use.
- ★ The parts that contact the materials are all made of imported stainless steel. The interior surfaced of the vessel is subjected to mirror polishing 300 EMSH, which is in accordance with sanitary requirements.

Components:

- PLC control system
- Four sealing wheels
- Cap sorting part and cap loading part machine frame
- No need to change accessories, suitable for round caps of various sizes
- 2 meter straight conveyor line (can do customized)
- Can be used with filling machine and labeling machine
- Conveyor, capping speed and capping time can be easily debugged
- This machine is made of stainless steel and is GMP-compliant and durable
- Can be made into a single-head capping or double head capping according to user needs

Parameter:

Item	Description
Applicable bottle specifications	Diameter 40 ~ 115 mm; Height 80-320mm(customized)
Bottle's neck diameter	20 ~ 55 mm(customized)
Production capacity	2000 ~ 3500 b/H(adjustable)
Power supply	AC380V 50/60 hz
Power	1.2 KW
Air pressure	0.4 Mpa
Single machine noise	70 db
Material	304 SUS&316L SUS
Automatic Grade	Automatic
Driven Type	Electric
Speed control	inverter control
Bottle Application	Round bottle, flat bottle, square bottle
Cap application	Screw cap, pump head etc