

4-axis Servo Horizontal Flow Wrapper V-TYPE-4V



4-axis servo flow wrapper. Can record wrap tension, sealing data and product data. Adjusting is humanize and fast.

FEATURES:

4 axes Servo driving system: End sealing unit, film transportation, feeding chain and film tension are driven by servo motors independently is durable, high productivity and low noise
User-friendly human / machine interface control with 10.4inch colorful monitor.
50 recipe (bag length, temperature, speed, feeding position, film tension and cutting position)
Self-diagnosis function, error message will show on screen for easy troubleshooting.
Overload sensing function for each servo motor prevents the parts and product from being damaged in advance.

OPTIONAL ACCESSORIES:

- Auto-feeding system.
- Date coder.
- Stainless steel machine frame.
- Auto-splicer.
- No-Product-No-Go
- No-Gap-No-Seal
- CE or UL standards.

SPECIFICATION:

MODEL	HP-350-4V	HP-450-4V	HP-600-4V
Operating Speed	20 - 300 pack/min		20 - 250 pack/min
Bag Length	50 - 750 mm		
Max. Film Width	350 mm (300 mm)	450 mm (300 mm)	600 mm (350 mm)
(max. roll dia.)			
Product Width (max.)	20 - 120 mm (50 - 150 mm)		80 - 230 mm (110 - 270 mm)
Product Height	Max. 60 mm (90mm)		Max. 60 mm (110mm)
Machine Dimensions	L3900*W1090*H1600	L3900*W1150*H1600	L3900*W1300*H1600
(L*W*Hmm)			