



XGYD series Washing Filler & Press Capper for Glass Bottled



The filler & capper is developed on the basis of digesting, absorbing and improving the advanced technology introduced from abroad, and up to international level. It is mainly used aerated water and so on. It is advanced in structure, steady and reliable in performance, high in production efficiency, and the speed can be regulated infinitely. It is the ideal equipment for drink factories of small and middle scale.

主要技术参数 Main Technical parameters

型号 Type	XGYD18186	XGYD24248	XGYD32328	XGYD404010	XGYD505012
生产能力(B/H) Proouctive capacity(330ml)	3000-6000	8000-10000	10000-12000	15000-16000	18000-20000
冲灌压盖头数(头) Heads of rinsing, filling&capping	18-18-6	24-24-8	32-32-8	40-40-10	50-50-12
适用瓶高 (mm) Suitable bottle height	160-340				
适用瓶径 (mm) Suitable bottle diameter	Φ50-Φ100				
冲瓶供水压 (MPa) Water pressure supply	0.25-0.35				
灌装形式 Filling way	等压灌装 Balanced Pressure filling				
灌装温度 (℃) Filling temperature	0-5				
灌装压力范围 (MPa) Filling pressure	0.15-0.5				
主传动电机功率 (kw) Main motor power	3	4	7.5	11	15
总功率 (kw) Total power	3.73	4.73	8.43	12	16
外形尺寸 (mm) Overall dimensions	2750×1950×2500	3100×2200×2500	4350×2700×2600	4850×3200×2600	5250×3846×2600
重量 (kg) Weighe	3800	5000	6800	8800	11000