

## *Premade Bag Rotary Packing Machine BF6300/BF8200/BF8250*



Applicable bag type: pillow bag, gusset bag, seal type bag.

Applicable film material: a variety of laminated films, single-layer PE film, film thickness range 0.04~0.15mm.

Applicable packing material: a variety of recreation frozen food, coffee bean, oatmeal, granulated sugar, salt, rice, pet food, small hardware etc.

### **Feature:**

- Automatic warning protect function, safer working environment and less materials losing.
- The frame of machine is made of #304 stainless steel, man-machine interface, easy to operate and maintained.
- Available system for choice: remote diagnosis system, automatic lubrication system, automatic clips adjusting system.

**Parameter:**

Item No.	BF6300	BF8200	BF8250
Working Station	8 stations	8 stations	6 stations
Packing Speed	10~60bags/min	10~60bags/min	10~60bags/min
Bag Size	L: ≤350mm	L: ≤400mm	L: ≤450mm
	W: 100~200mm	W: 140~260mm	W: 200~320mm
Station Function	bag feeding, date printing, bag opener, proudcts filling, backup, backup, sealing, output	bag feeding, date printing, bag opener, proudcts filling, backup, backup, sealing, output	bag feeding, date printing, bag opener, proudcts filling, sealing, output
Gas Pression	0.8MPa	0.8MPa	0.8MPa
Gas Consumption	0.6m <sup>3</sup> /min	0.6m <sup>3</sup> /min	0.6m <sup>3</sup> /min
Voltage	2.5KW/380V/50(60)Hz	2.5KW/380V/50(60)Hz	2.5KW/380V/50(60)Hz
Machine Size(mm)	L*W*H=1610*1510*1480	L*W*H=1640*1510*1510	L*W*H=1610*1510*1480
Machine Weight	1350KG	1400KG	1500KG