



## *Candy Wrapping Machine ZE-250/350/450/600*



Automatic horizontal packing machine suitable to pack all kind of solid and regular material, such as biscuit, cake, bread, moon cake, custard pie, fruit pie, instant noodle, sweet, medicine, daily product, hard ware, plastic toy and so on.

Our machine adopt colored touch screen , perfect interface between operator and machine adopt big colored touch screen, digital temperature controller system, easy to set parameters and easy to operate for changing different size products world brand high sensitivity photocell tracking system, to control products position exactly. Electrical professional design, easy control and more stable. Mechanical professional design, easy operating and improving productivity.

### **Features**

1. Main control circuit adopts developed by our company PLC, color touch screen display, inverter control, perfect interface between operator and machine. That make operation and adjustment easily.
2. The packing speed and the length of the bag are controlled by the double frequency converter. Step-less variable speed, wide adjustment range, can be a perfect match with the production line of the former process.
3. High sensitive electric eye is the function of automatic tracking bags length accurately, no manual adjustment after setting.
4. Each seal temperature is independent of control. It is suitable for a variety of packaging materials. The sealing is beautiful and firm. In addition, According to the user's need to configure the code machine to print production date, batch number and so on.

## Technical Data

<b>Model</b>	<b>ZE-250</b>	<b>ZE-350</b>	<b>ZE-450</b>	<b>ZE-600</b>
<b>Film width</b>	Max.250mm	Max.350mm	Max.450mm	Max.600mm
<b>Bag length</b>	30-110 or 90-220mm	90-220 or 150-330mm	180-440mm	130-450mm
<b>Bag width</b>	30-110mm	50-160mm	50-190mm	110-280mm
<b>Product height</b>	Max.55mm	Max.70mm	Max.90mm	Max.100mm
<b>Packing speed</b>	30-230 bag / min	30-200 bag / min	30-180 bag / min	30-150 bag / min
<b>Power supply</b>	220V 50/60Hz	220V 50/60Hz	220V 50/60Hz	220V 50/60Hz