

## LS shrinkable sleeve labeling machine



As the best China LS shrinkable sleeve labeling machine supplier, Grepack provides quality LS shrinkable sleeve labeling machine to global clients

## **Description:**

- 1. Electronic and optical fiber eye: tail surface and electronic eye are combined to improve the cutting precision.
- 2. The change of cutting head is divided into three parts according to the diameter of the bottle:
- (1)25-50mm
- (2)50-95mm
- (3)95-125mm

Within the range of the specification, only blade needs changing and its rapid and convenient. By touching the screen, automatic searching and position is applied.

- 3. Bottle carrying positioning system: led belts are applied to transmit bottles and simultaneously adjust the machine to control the highly sensitive screen operation with people-controlling machine. After the label is cased, it is made smooth by the brushes. The operating speed of the fixed bottle-carrying belts can be controlled simultaneously with that of the conveyer.
- 4. Microcomputer is used to control the machine at a constant temperature so that time and power is saved. The stove can be opened and cleaned during to the production. Rolling stone is separated by glass fiber and the outer part does not radiate heat to ensure safety. Both temperature and wind power can be adjusted according to the height of conveyer. Rapid heating and thermostatic contacting characterize contracting stove. Either steaming or electro thermal power can be used to contract.

## **Technical Parameter:**

Model	LS series
Main engine size	1100*1300*2000mm
Main engine production speed	100bottles/min 250bottles/min 400bottles/min
Main engine power supply	380V 220V
Main engine power	1-2.5kw
Shrink power	15KW
Label length	25mm-280mm
Label thickness	0.035mm-0.13mm
Label material	PVC,PET,OPS
Bottle height	15mm-320mm
Bottle diameter	28mm-125mm
Bottle Shape	Round, square, elliptic,rectangular