

Automatic Band Sealer FRB-770III



FRB-770III is continuous band sealer with a purpose-made Sealer Stand. That enhance the band sealer's functionality and ergonomics. Industrial-grade machines designed for light-duty continuous bag sealing applications. FRB-770 will seal bags made with thermoplastic materials including Polyethylene (PE), Polypropylene (PP) and heat-sealable laminations. FRB-770III has height-adjustable stands which position the band sealer for optimal ease of operation, comfort, and safety. Compact and stable, equipped with casters to ease movement and work area positioning.

- All-metal construction
- Can be paint hull or Stainless steel hull
- Can remove the stand to be horizontal type FRB-770I
- Quick and easy to install
- Compact footprint
- Equipped with lock-in screws for height adjustment
- Caster wheels for ease of movement
- Base-compatible predrilled screw-in holes to secure sealer to stand
- Seals thermoplastic materials including Polyethylene (PE), Polypropylene (PP), BoPET (ie. Mylar), and heat-sealable laminations and cellulose (ie. Cellophane)
- Capable of speeds of up to 12 mts/min (40 ft/min) , depending on product/bag seal characteristics

Parameters:

Model	FRB-770III
Voltage (V/Hz)	AC 220/50 110/60
Power (W)	50
Sealing Power (W)	300×2
Sealing Speed (m/min)	0-12 (0-16)
Sealing Width (mm)	10
Temperature Range (°C)	0-300
Printing Type	Steel wheel for embossing printing (optional)
Distance from Sealing Center to Conveyor Table (mm)	20-40
Conveyor Table Size (L×W) (mm)	840×153
Overall Conveyor Loading (kg)	≤3
External Dimensions (L×W×H) (mm)	840×550×800
Net Weight (kg)	29