

HY-420 Automatic thermoforming Sealing Packaging Machine



Features

1. The machine works smoothly and continuously, and is suitable for sealing all kinds of masks, medical supplies, sanitary products and other products.
2. Automatic bagging, photoelectric correction, no burr, mold forming.
3. The equipment can be configured with different types of feeder.
4. Mitsubishi PLC imported from Japan can improve the accuracy and stability of the equipment.
5. Intermittent sealing is better to ensure the sealing beauty and avoid leakage.
6. The machine is easy to operate, PLC touch screen, according to the packaging material, product thickness and length to adjust the packaging temperature and speed. Servo motor. Through the control of light, electricity and gas, the fault can be self diagnosed and displayed clearly. The language of the operating system can be Spanish, French, Korean, Russian, Japanese, Arabic and other local languages.
7. The whole machine is covered with stainless steel, with good appearance, easy to clean and durable. The cost of operation and maintenance is low.
8. Intelligent PLC temperature control.
9. Automatic alarm for required quantity, automatic batching and stacking for required quantity.

Technical Parameters

model	HY-420
Production speed	30-400 bales / min
Bag packing type	Quadrilateral seal
Dimensions of packaged products	(length) 5-400mm (width) 5-300mm (height) 1-60mm
Calculation formula of film width	According to the mold
Calculation formula of bag length	According to the mold
Film width	≤435mm
Outer diameter of packaging film	≤400mm
Packaging film material	PE composite pet
pressure	6Mpa
Machine operating height	930mm
Total power	14.5KW
Type of power supply	380V 50 / 60Hz three phase
Machine weight	2600kg
Machine dimensions	6520x1060x1720mm (L x W x H)