

i-Sleeve Single-head Auto Shrink Sleeve Applicator Machine / Labeler



A single head Shrink Sleeve Applicator machine which sets the standard speed up to 150bpm. Ultra-thin cutter plate, unique drive transmission structure design, easy adjustment and disassembly.

Machine Features

- Can be fully integrated within production line.
- Safety guards and touch panel control system ensure unit is user friendly.
- Specially designed cutter plate does not need changing within rated specifications. If necessary, changes can be accomplished in only three minutes.
- Forceful insertion design could lower production costs for you.
- Integrated adjustment design for the entire transmission maximizes versatility for accommodating different label specifications.
- Accommodates film paper core size from 5"-10" with variable adjustments.

Innovative Features

- Slim cutter plate design, with fixed drive belt tension design, for easy adjustment and maintenance.
- Manual up and down spiral design for easy adjustment. Adjustment range is wider than traditional machines.
- With unique drive transmission structure, designed for easy usage.
- Machine only uses 3 timing belts for easy maintenance.
- Adopts separate conveyor design, which can easily be integrated within any production line.

Specification

Max speed	150BPM
Bottle Diameters	ψ25mm~ψ125mm
	(Based on the bottle dimension of specification provided by the customer)
Film Material	PVC /PET /OPS
Film Width	PVC: 0.035mm~0.08mm, PET: 0.04mm~0.06mm,OPS:
	0.04mm~0.06mm
Machine Size	730mm*860mm*1900mm(L*W*H)
	(Dase-Sing reserves the right to mofify the apperarance and dimension of the machine, in order to optimize the fuction of the requirement)
Voltage	3P;220V
	(According to customer requirement)