



Three Side Sealing Powder Packing Machine DXD-F150C



Features:

1. The fully automatic three side sealing powder packing machine comes with PLC programmable control and an English and Chinese display screen, making it easy to operate and maintain. It is easy to adjust.
2. A photoelectric tracking system and two-way compensation function of the three side sealing powder packing machine ensure correct and accurate double-face printing and counting.
3. The powder packer shell, made of full stainless steel, is highly corrosion proof, and easy to clean.
4. The packing machine uses a measuring cup for dosing.
5. Options for cutting way: flat cutting, saw-tooth cutting, dashed line cutting
6. Options: ribbon coding machine

Usage:

This three side sealing powder packing machine is used for packing loose, non sticky powder materials such as milk powder, coffee powder (without sugar), flour, and more. It is used in the pharmacy, food, dairy, and agriculture industries.

Main Technological Parameters:

Item / Model	DXD-F150C
Bag length	80-200mm (adjustable)
Bag width	70-140mm (should change bag former)
Packing speed	30-60bags/min
Packing dosage	40-200ML
Applicable film	PET/AL/PE, PET/PE, NY/AL/PE, NY/PE
Max. film width	300mm
Max. film diameter	Φ300 mm
Film core diameter	Φ70-76 mm
Electric source	380V 50Hz
Total power	1.8 Kw
G.W.	410Kg
Package size	1300×1100×1200 (L×W×H)