

## RS - 460E automatic shrink machine



**Packaging machine features:** the machine is fully automatic sleeve type machine is on a single object or without tap product design, this machine can automatic docking with the line feed, wrapping film, sealing and cutting, shrinkage, finalize the design, automatic packaging equipment without manual operation. Suitable for paper boxes, bottles, plastic boxes and other products in a box, no tap (or tap) heat shrinkable packaging; With constant temperature contraction PE furnace at the same time, make the goods perfect packaging.

**Technical features:** sealing knife with Teflon coating antis ticking high-temperature alloy knife, sealing and cutting without mucous membrane, sealing strong, coking, don't smoke, to ensure that the working environment of zero pollution. Prevent overheating compensation device effectively prolong the service life of equipment; The clamp hand safety protection function can prevent the mistake packing materials, and ensure the safety of the operator. This set of equipment with large screen touch screen man-machine interface, Siemens PLC program controller, and the kind of cylinder, the machine running stable and reliable performance suitable for PE, POF. Any such as PVC shrink film mining

**Applicable industry:** suitable for electronics, software, food, and beverage, pharmaceutical and other industries.

### Technical parameters:

Model	RS-460E
Inner size	3Phase 220V/380V,50HZ-60HZ
Power	3KW
Packaging speed	0-10 Packing/minute
Working air pressure	250L/min 0.4-0.6mpa
Membrane width	Max590mm/0.03-0.25mm
Sealing and cutting length of the cutting tools	600mm
Max Packing Dimensio	400 (L) x300(W)x200(H)mm
Min Package size	250 (L) x50(W)x100 (H) mm
Machine Dimensions	1060x1600x1930mm The merger of the two machine within 2 meters
Specifications of conveyor	900(L)x306(W)x800(H)mm
Machine weight	370KGS
Shrink film	PE,POF,PVC,PP