



## *Vertical Form Fill Sealing Machine AP-600L*



This model is manufactured using superior grade stainless steel procured from trusted & approved sources of the market. Due to our sound infrastructure and in-house design unit we have been able to offer our clients with exactly what they require. Our range of machines is renowned for high efficiency and durability. We make sure that only defect less range reaches the market so that our customers can get good value for their money.

### **Salient Features:**

- Faster film drawing done through servo based and electromagnetic clutch and break film drawing mechanism
- Highly efficient and reliable
- Designed with stainless steel
- Four side sealing helps excellent packaging

**Technical Specifications:**

<b>Machine speed</b>	Up to 75 SPM depending on the product & sachet/pouch dimension.
<b>Packing range</b>	Suitable to pack up to 200 ml and depending upon product to be packed
<b>No. of tracks</b>	Up to 7 tracks depending on sachet/pouch width
<b>Max. roll width</b>	600 mm
<b>Max. roll dia</b>	350 mm
<b>Max length of pouch</b>	Up to 200 mm
<b>Film draw mechanism</b>	<b>Options</b>
	a) Servo based
	b) Electromagnetic clutch and break
<b>Web controller</b>	<b>Options</b>
	a.) Electronic web edge control.
	b.) Pneumo hydraulic web edge controller
<b>Compressed air</b>	2CFM @ 6 kg/cm sq.
<b>Electrical power required</b>	Up to 6KW
<b>Main Body Frame</b>	<b>Option</b>
	- MS with Powder coating.
	- MS with SS cladding
<b>Type of Sealing</b>	4 Side Sealing
<b>Machine dimension</b>	2830 mm X 1300 mm X 2000
	(Height mm X Width mm X Length mm)
<b>Net weight</b>	1800 kg