



## *Automatic Carton Erector and Closing Machine*



### **Features**

- Optimum speed – 120 Cartons/Minute.
- Easy & fast changeover.
- Automatic leaflet insertion device.
- High level of adaptability for various applications

### **Consumption**

#### POWER CONSUMPTION:

Max. - 1.5 KW excluding vacuum pump

#### AIR CONSUMPTION:

Max. - 100 LPM @ 2 kg/cm<sup>2</sup>

VACUUM REQUIREMENT – 650-700 mm of Hg.

#### **STANDARD FEATURES WITH MACHINE**

Automatic carton erection  
Automatic tube feeding  
Inbuilt check devices  
Automatic coding on the tubes  
Machine SS 304 guards  
Inbuilt centralized lubric  
No product no carton  
No carton product by-pass  
No leaflet no carton  
Product overload machine stop  
Ejection of empty carton  
Designed to handle both reverse & straight cartons

#### **OPTIONAL FEATURES WITH MACHINE**

Closing of cartons by hot melt adhesive  
Tubular cover – Aluminium or SS 304  
Machine interconnections with tube filling machine  
Electronic product counter & time totaliser  
Flame proofing  
Brush insertion  
Automatic leaflet insertion device in carton  
GMP Version  
PLC based machine operation  
Automatic inkjet printing operation

### **Machine Weight**

PAC Cartoner -1800 KGS