



## T- Series Turbine Heat Circulation Shrink Tunnel



T-Series shrink tunnel produces consistent uniform film shrink using heavy-duty, variable speed blowers and heating elements. This combination creates a recirculating air system that forces air to all package surfaces. Independent control systems regulate temperature, air velocity and conveyor speeds. The efficient heating system on each machine reduces the amount of electricity and the cost of operation.

### Features:

- Turbine heat circulation system design
- Reduce heating time
- Lower heat lost
- Diminish the use of electricity
- The lateral air flow directions are adjustable.
- Bottom air flow strength can be manipulated.
- Different conveyor systems are available (live roller, stainless steel or teflon mesh).

Model	T-61	T-62	T-63
<b>Machine Size</b> L x W x H (mm)	1450 x 860 x 1080	1700 x 900 x 1160	2200 x 1070 x 1230
<b>Chamber Size</b> L x W x H (mm)	1100 x 300 x 200	1200 x 350 x 280	1700 x 440 x 350
<b>Packing Size</b> W x H (mm)	280 x 150	300 x 230	400 x 300
<b>Voltage</b>	380V / 3PH	380V / 3PH	380V / 3PH
<b>Power (Kw)</b>	11 Kw	14 Kw	16 Kw
<b>Operating Power</b>	4 V	5 V	8 V
<b>Conveyor Speed (m/min)</b>	0-30	0-30	0-30

<b>Model</b>	<b>T-64</b>	<b>T-65</b>	<b>T-1200-280</b>
<b>Machine Size</b> L x W x H (mm)	2200 x 1090 x1230	2200 x 1250 x 1230	2400 x 1660 x1160
<b>Chamber Size</b> L x W x H (mm)	1700 x 540 x 350	1700 x 700 x 350	1900 x 1200 x 280
<b>Packing Size</b> W x H (mm)	500 x 300	650 x 300	1050 x 230
<b>Voltage</b>	380V / 3PH	380V / 3PH	380V / 3PH
<b>Power (Kw)</b>	18 Kw	23 Kw	28 Kw
<b>Operating Power</b>	10 V	10 V	12 V
<b>Conveyor Speed (m/min)</b>	0-30	0-30	0-30