

ZLZ SERIES VACUUM MILL, STATIONARY



THIS EQUIPMENT, MAINLY USED FOR SOLID MATERIAL TRANSFERRING AND CHARGING, CAN BE MATCHED WITH FBG OR FBD BOWLS. IT CAN SORT OUT QUALIFIED PARTICLES ACCORDING TO TECHNICAL REQUIREMENTS BY VACUUM CONVEYING. MEANWHILE, IT IS WIDELY USED IN PHARMACEUTICAL, CHEMICAL AND FOODSTUFF INDUSTRIES.

FEATURES

- 1. INTEGRATED WITH DRY MILL
- 2. WHOLE PROCES ANTI FALLING SYS
- 3. INTEGRATED WITH VACUUM CONVEYER

ADVANTAGES

- 1. ON LINE MILLING
- 2. DOUBLE SAFETY
- 3. CLOSE SYS FOR EASY MATERIL CHARGING AND DISCHARGING

MAIN TECHNICAL PARAMETER

Model		ZLZ100	ZLZ200	ZLZ450
L1		415	415	500
L2		805	805	1090
W1		600	600	700
H		3470	3470	3788
H1		2300	2300	2450
H2		2550	2550	2800
H3		347	347	485
Ф		200	200	200
Lifting Power	kW	0.75	0.75	1.5
Miller Power	kW	0.75	1.1	3
Miller Capacity	kg/h	100	200	450
Mesh Size		5~30	5~30	5~30
Total Weight	kg	370	370	450