

Rotary Tablet Press Machine KTMSA-series



Feature:

- Quiet Running Through Precise Rail and Turn Table.
- Low Vibration by Strength Design of a Frame.
- The Convenient Operation Panel. The functional switches and signals are integrated in 10" Touch Screen to make it possible that machine is Convenient Operated.
- The middle agitating hopper and the direct-hitting feeder with three paddles provide any kinds of powder uniformly, so that the deviation of content can be minimized while loading.
- The middle board on the lower punch cartridge can be separated so that you can exchange the rack effectively and speedily.
- The cover of the upper punch and the dust-collecting duct protect the machine from dust and prevent alien substances from adulterating.

Specifications:

Model	KT30MSA	KT36MSA	KT45MSA
Number of Station	30	36	45
Dia tablet speed(r.p.m)	10-60	10-70	10-70
Tablets/hr	18,000-108,000	25,200-151,200	27,000-189,000
Type of tooling	EU-D	EU-B	EU-BB
Max. table dia.(mm)	25	16	13
Max. pressure dia.(ton)	Pre 10 / Main 10	Pre 10 / Main 10	Pre 10 / Main 10
Max. filling depth(mm)	18	18	18
Main motor(kw)	7.5	7.5	7.5
Dimension (W x D x H mm)	1,050 x 1,150 x 1,905	1,050 x 1,150 x 1,905	1,050 x 1,150 x 1,905
Weight(kg)	3,9	3,9	3,9