



## *Transparent Film Packing Machine CW-650*



This Transparent Film Packing Machine for Box can finish automatic packing, feeding, folding, heat-sealing, counting and automatically sticky tear tape in one machine. Running speed can be adjusted stepless. Only need to change few parts can wrap different box size (dimension, height, width). The machine can be connected with cartoning machine in line.

Transparent Film Packing Machine For Box is widely used in packing single-box or collective boxes of various box-types of medicine, health care products, food, tea boxes, cosmetics, stationery, audio-visual products and other industries. Such as medicine, poker, cigarettes, VCD box, tape, cosmetics box, tea box, napkins box, etc.

### **Features:**

- The film loading and film drawing device use servo motor, it is more accuracy.
- The box pushing device is equipped with box get stuck protect part, it will jump off and stop automatically, which can ensure the integrity of the boxes.
- It can wrap different box sizes. only need to change 4 parts for different size, The push plate, The film fold plate, The angle making mould, The heat sealing plate stable performance and convenient operation and maintenance
- Adopt multifunctional digital frequency transformer and the speed can be varied infinitely.
- High filling accuracy, Adjustable and stability, beautiful, tidy, solid, and health packing appearance.
- The machine can be connected with cartoning machine in line.
- Stainless steel 304 machine body and organic glass cover.
- Tear tape, ink printer, box turning over and stacking are optional.

**Specification:**

| <b>Model</b>       | <b>CW-650</b>                           |
|--------------------|---|
| Tube material      | BOPP film and golden tear tape          |
| Packing Speed      | 15-30 pcs/min                           |
| Filling Size Range | (L) 100-400mm (W) 45-240mm (H) 20-115mm |
| Power              | 4.5KW                                   |
| Reject rate        | <=+-1%                                  |
| Voltage            | 220V/1Phases/50/60HZ Or customized      |
| Air Pressure       | 0.6-0.7Mpa                              |
| Dimension (LxWxH)  | (L) 2180mm (W) 1000mm (H) 1500mm        |
| Weight             | 800kg                                   |