

GXT-4 Filling and Capping Machine with Labeling



This production line is suitable for the filling production of small batch multi-gauge, liquidity or viscous materials. It only needs 2 operators to complete filling, capping, labeling and packing. The line structure is compact, small footprint, which will help the workshop planning and adjustment.

GXT-4 Filling Capping Labeling Machine is made of high-quality stainless steel SUS304, with excellent anti-corrosion performance. The machine consists of four independent operation of the pneumatic piston filling unit, rotary alternating grasping, capping head and cover cap device and the cylinder pressure bottle institutions, self-adhesive labeling agencies. Filling, capping and labeling can be done once. The whole machine has the advantages of compact structure, small area, easy cleaning, simple operation and convenient and quick change of product. It is suitable for the filling production of non-viscosity or high-viscosity materials of multi-product and small-batch, which can save the most. Human resources (1 person can operate).

Main Parameters:

| Applicable bottle diameter | Ф40-90 mm H: 80-230 mm |
|----------------------------|--------------------------------|
| Cap Specification | Ф20-50 mm H: 15-30 mm |
| Label size | L: 50-320 mm W : 20-140 mm |
| Volumes | 80~1000 ml |
| Measure precision | ±1% 200 ml , ±0.5% 200-1000 ml |
| Label precision | ±1 mm |
| Production capacity | ≦1000 bottles / hour |
| Air pressure | 0.5-0.7 Mpa |
| Power source | 220V, 50Hz |
| Total power | 3.0 KW |
| Weight | 1200 KG |
| External dimensions | 2430*2000*2400 mm (L*W*H) |