



## *KD-260/350/450C Pillow Packing Machine*



### **Features:**

1. The pillow packing machine adopts with PLC controller, makes the whole machine runs programmed.
2. All the information including speed of main engine, bag length setting and compensation amounts display on the TD-200 screen.
3. The bag length can be set on the TD-200 screen, and the computer will adjust bag length automatically.
4. The pillow-style packing machine checks color code with imported photoelectric detection sensor. With PLC and bi-directional compensation mechanism to track, so that benchmarking is fast and accurate.
5. The pillow packing machine can control the temperature with automatic temperature controller, so as to improve the sealing quality.
6. The machine is suitable for various kinds of aluminum plastic sheets.

**Parameters:**

Max Film Width (mm)	260	350	450
Max Packing Capacity (sheets/min)	120	50 to 60	50 to 160
Suitable Film Thickness (mm)	0.04 to 0.06	0.03 to 0.06	0.03 to 0.06
Length of Bags (mm)	50 to 330	65 to 330	65 to 330
Packing Width (mm)	25 to 100	25 to 150	25 to 200
Packing Height (mm)	≤35	5 to 80	5 to 80
Total Power	2.7kW 220V	3.2kW 220V	3.7kW 220V
Overall Dimension (L×W×H) (mm)	3500×880×1500	4000×1050×1560	4200×1200×1750
Weight (kg)	500	600	680