

Compact Toothpaste Tube Filler



Metal hose filling and sealing machine, the main use of metal hose as a packaging material of the quantitative filling, sealing. This machine is widely used in pharmaceutical, cosmetic, food, chemical and other industries packaging. Such as: ointment, adhesive, AB glue, neoprene, epoxy glue, skin cream, hair cream, shoe oil, toothpaste and other liquid or paste material filling and sealing.

Description:

Aluminum tube filling and sealing machine used for Aluminum Tube is one of main latest products of our company. It is full automatic. This machine can be used for filling cream and liquid materials, and it is characteristics with firm filling, high precision of dosage. The three functions of filling, sealing and batch numbering can be automatically completed. It is widely used in pharmacy, daily chemical, food, chemical industries, such as for filling pharmacy cream, hair color ante, toothpaste, leather oil, glue, AB glue, Nanp-epoxy adhesive, Neoprene adhesive etc. Convenient and quick dosage adjustment, high efficiency, good-looking, compact structures are the features of the machine. The tube cups can be adjusted according to the tube dimensions. The important parts of the machine which contact directly to the filling material are made of stainless steel (SUS304 is for general use, and SUS316L is for pharmacy use). A special valve makes this machine be suitable for filling cream and liquid material. It is an ideal and economical filling machine in the pharmacy, daily chemical, fine chemical and other fields.

Automatic Tube Filling Sealing Machine uses rotary piston way, filling precision, using light point control, folding sealing, all work with high precision cylinder full stroke control, easy to adjust filling volume, the filling speed can be adjusted. It applies to all kinds of composite tubes, plastic pipe and metal pipe filling and sealing, date printing, cut the tail. Folding neat appearance, folding strong, high accuracy, good stability. According to the different material properties, Optional ingredients bucket heating system, anti-leak filling head Machine, adopts imported PLC control, import the original frequency control.

主要技术参数 TECHNICAL PARAMETER

电源 Power supply	220V、50Hz
生产能力 Capacity	10~30支/分 10~30 pcs/min
線接前限 Filing volume	20 ~ 150ml
就發產品 Aluminum tube diameter	Φ13 - Φ32mm
电机动率 Motor power	1.5kw
工任税 Working positions	16
康·爾 Weight	250kg
外形尺寸 Dimension(L×W×H)	1700 × 1000 × 1700mm