

3-axis Servo Horizontal Flow Wrapper V-TYPE-3V



3-axis servo flow wrapper. Seal data, product data can be recorded. Adjusting is simple and fast.

FEATURES:

- 3 axes Servo driving system: End sealing unit, the film transportation and feeding chain are driven by servo motors independently.
- User-friendly human / machine interface control with 8.4inch colorful monitor.
- Independent control of bag length, cutting and feeding make the production changeover easy and quick.
- 50 sets product data memory.
- Servo driving controlled for accurate bag length.
- The parameter of feeding position is set up and saved via the touch screen and it will be auto positioning whenever production changeover.
- Driving transmission parts are largely eliminated resulting in considerable reducing the noise, vibration, maintenance and enhance the accuracy and running capacity.

OPTIONAL ACCESSORIES:

- Auto-feeding system.
- Date coder.
- Stainless steel machine frame.
- Auto-splicer.
- CE or UL standards.

SPECIFICATION:

MODEL	HP-350-3V	HP-450-3V	HP-600-3V
Operating Speed	20 - 250 pack/min		20 - 150 pack/min
Bag Length	50 - 750 mm		
Max. Film Width	350 mm (300 mm)	450 mm (300 mm)	600 mm (350 mm)
(max. roll dia.)			
Product Width (max.)	20 - 120 mm (50 - 150 mm)		80 - 230 mm (110 - 270 mm)
Product Height	Max. 60 mm(90mm)		Max. 60 mm(110mm)
Machine Dimensions	L3860*W940*H1560	L3860*W1000*H1560	L3860*W1130*H1560
(L*W*Hmm)			