



Automatic Packing Machine WP-HT(ET)5235



Feature:

- 1) Attractive standing bag style to satisfy the market demand.
- 2) It completes bagging sealing, bottom flat automatically.
- 3) PLC pneumatic system for vertical and horizontal sealing.
- 4) Easy to operate, low maintenance.
- 5) Applicable bag type: the machine can make pillow-type bag and standing bag according to customer's request.

Appliation:

- 1) Applicable Bag Type: seal type bag.
- 2) Applicable Film Material: a variety of laminated films, single layer PE film, film thickness range 0.04~0.15mm.
- 3) Applicable Packing Material: granule, food and non-food, such as potato chips, candy, milk powder, frozen food, pet food, oatmeal, small hardware and so on.

Specification:

Item NO.	WP-HT5235	WP-ET5235
Film Width	220~520mm	220~520mm
Sealing Width	5~10mm	5~10mm
Front Surface Width	60~190mm	60~190mm
Side Surface Width	40~110mm	40~110mm
Max. Film Length	350mm	350mm
Packing Speed	50bags/min	45bags/min
Film Pulling Driven System	servo motor	servo motor
Horizontal Sealing Driven System	servo motor	cylinder
Voltage	6KW/220V/50(60)Hz	5KW/220V/50(60)Hz
Air Pressure	0.6MPa	0.6MPa
Air Consumption	0.3m ³ /min	0.7m ³ /min
Machine Size	1820*1255*1954mm	1820*1255*1954mm
Machine Weight	700kg	680kg