


Fully-auto Gable Top Carton Filling Machine GTP-2000/3000



- Simple design, only need one operator, low-cost maintenance
- Standardized parts, localized replacement
- Short time for changing box size, high filling precision, with fine turning device
- Compact design, less space required, low noise, low energy consumption
- PLC control, easy operation, flexible
- Guaranteed after-sales service and spare parts supply
- Meeting USA 3A standard
- Adjustable production speed, filling volume and box height, high adaptability

Equipment Configuration:

- Stainless steel shell structure
- Mechanical drive system automatic getting and putting box
- Touch screen PLC program control computer, vacuum box part magic eye identification device
- Automatic induction switch with no paper box no fill
- Safety shield, electrical control since
- Stainless steel products to lock the door when you switch cylinder and level of pneumatic valve control
- Standard diversion filling lips and filling fine-tuning institutions
- Hot air seal top and bottom
- Water cooling molding rods, sealing clamp
- Electrical control motor speed to realize the mechanical standard zero adjustment speed variation
- To foam motor and vacuum generator
- High, medium and low level control and low level to be automatic alarm, stop advice
- Automatic paper box absorption to spurt the code machine
- Liquid level controller, low level alarm
- With filling system CIP cleaning accessories
- Centralized power supply lubrication system

Parameter:

ITEM	GTP-2000	GTP-3000
Production Capacity	2000box/h—250 or 500ml	1000box/h—250 or 500ml
	1000box/h—1000ml	500box/h—1000ml
Air Consumption	85psi/7bar, 4.0scfm/113lpm	85psi/7bar, 6.5scfm/184lpm
Cooling Water	50f/10°C, 2.0gpm/7.6	50f/10°C, 2.0gpm/7.6
Power	26kw	30kw
Control Method	Semi-automatic PLC control	Fully-automatic PLC control
Dimension	3500×1500×2800 (mm)	3500×1500×2800 (mm)
Weight	2450kg	2460kg