

TODAY MACHINE

Simple & Responsible Since 2001

Horizontal Wrapping Machine/Flow Wrapper FW-series



Biscuits, rice Krispies treats, snow cakes, breads, instant noodles, rice noodles, daily necessities, tissues, sanitary towels, industrial parts, paper boxes, tray...

Character:

Dual servo motors and single frequency conversion control, bag length can be set and cut in one step, saving time and film.

Automatic stop in case of material absence, run film cutter stop, push material automatic make up.

Temperature control module inside, temperature independent PID control, accurate and suitable for packaging different material.

Prevent from cutting material function without stop, prevent from cutting material, improve the operating efficiency of the machine and reduce equipment loss.

Touch interface, easy and quick setting and operating. Self failure diagnosis, clear failure display. Positioned stop function, without sticking cutter or wasting film.

All control is realized through software, easy for function adjusting and technical upgrade.

Option:

- Date coder
- Gas flushing device
- UV sterilization
- Alcohol Spraying
- Extruder device
- Stacking device
- Turntable device

Technical data:

Model	FW-140	FW-240	FW-280	FW-320
Speed	<500	30-220	30-220	30-220
(pcs/min)				
Max film width	140	240	280	320
(mm)				
Bag size	L: 45-80	L: 75-190/150-350	L: 85-210/170-380	L: 110-250/200-420
(mm)	W: 60-100	W: 40-100	W: 40-125	W: 40-150
	H:6-12	H: <35	H: <45	H: <55
Power	220V 50-60Hz	220V 50-60Hz	220V 50-60Hz	220V 50-60Hz
	Single phase	Single phase	Single phase	Single phase
Power consumption(kw)	3.5	2.8	2.8	2.8
Size	3800x1350x1450	3900x840x1330	3900x840x1330	3900x840x1330
(mm)				
Weight	980	600	600	600
(kg)				