




M-210 Automatic Pre-made Pouch Packing Machine



The wrapping machine is under control of PLC. Can realize the filling of powder, granules, water aqua and mini-viscous liquid. It is suite for shapped-bag packaging .The wrapping machine also can realize the three-side sealing and four- side sealing easily. The wrapping machine is the most ideal bag-packaging machine up to now.

Performance advantage:

- ◆ Control system---The wrapping machine adopts Mitsubishi PLC control system, Filling dose random fine-tuning
- ◆ Control panel---The wrapping machine is equipped with colored touching-screen, easy-operated , stable and reliable
- ◆ Temperature control---The wrapping machine uses digital temperature control is intuitive form.
- ◆ Work-bin design---The wrapping machine can realize automatic detection. (Full, automatic stop feeding ;Less, automatic feeding).(The powder feeding machine is the matching product, the expense is extra)
- ◆ Filling exchanging---The wrapping machine can realize various kinds of filling including powder, granules, liquid, and micro-viscous liquid by exchanging filling head.
- ◆ Electrical elements---Adopting international famous brand to -ensure the remarkable quality, stability and high precision.
- ◆ Machine elements---The parts contacted with the material use the 316 high-quality stainless steel and non-poisonous, anti-corrosive PTEF hose. Other machine parts use the 304 high-class stainless steel.

Including the following components:

- Bag-sending shelf
- Standard horizontal strip heat- sealing device
- Easy tear cutting
- Vacuum opening device

Automatic material level controller
Photoelectric tracking detection device
LCD screen operation system
Micro-computer control system
Frequency conversion control system
Packing product education device
Date hard- pressing system

- ◆ Product requirements ---Molding film bag . (shapped-bag for customers own)
- ◆ Maintenance condition---The wrapping machine fully accords to the GMP requirements, easy to disassemble and clean.
- ◆ Real-time alarm---The wrapping machine can realize automatic alarming when the fault happens, automatic stops and alarms when the system appears serious breakdown
- ◆ Appearance design---The wrapping machine dopts high-quality organic glass and maintenance door, convenient operation, beauty and generous

Main technical paremeter:

- ◆ Max size: 212(w)x300mm(h)
- ◆ Min size: 90mm(w)x110mm(h)
- ◆ Packing material: heat sealing pre-made pouch
- ◆ Pouch format: doy pack, flat bag, hanging hole and zipper
- ◆ Maximum packing measure: 1000ml(powder according to the proportion of powder materials have different weight)
- ◆ Voltage: 380V/50Hz
- ◆ Power: 4.5Kw
- ◆ Filling error: $\leq \pm 1\%$
- ◆ Filling speed: 30-60bags/min
- ◆ Air-consuming amount: 0.6 m³/min
- ◆ Overall Dimension: 3120x970x1400mm
- ◆ Machine weight: 1100kg