

YS-BS-14D-CP-P Vertical Packaging Machine



This series machine is high speed, it can be integrated with various filling systems, suitable for many kinds of products with small bag but very fast speed.

- Continuous pull film movement, Simple structure, Economical and practical
- Continuous motion leads to high productivity
- Lean machine concept enables cost-effective production
- Maintenance-free servo-technology ensures reliable production
- PLC controls enable precise machine movements for smooth production and good bag quality
- Intuitive HMI allows easy operation and short training time
- Open machine concept for easy access and maintenance
- Compact machine design for good ergonomics, product-conserving filling and saving space

Technical Parameters

Model	YS-BS-14D-CP-P
Bag type	Pillow bag, double lines
Standard capacity	10-120 bags/min per line, total 20-240 bags/min
Bag size	Width : 65-140mm
	Length: 60-300mm
Film parameter	packaging material:OPP/AL/PE, PET/VMPET etc.
	Film width:max 300mm/line
	Film diameter: ≤400mm
	Core diameter:76mm
Total power	5 KW
Air pressure	≥0.5MPa
Air consumption	HS closure, 0.35NL/cycle

Outer dimensions (appr.)	1800*1270*1615mm
Weight (appr.)	800kg
Power supply (optional)	3N-PN-50Hz 380V/220V (3P 5 wires)