

YBZ-250B Automatic Blister Packing Production Line



According to the latest demand of the market, scientific research technicians of our company designed and developed the line machine, which is specially for al/pl bolster; pillow bag and packing into cartons.

Features

The line machine integrating al/pl blister; pillow bag, detection, rejection, and cartooning packing into an organic whole, which with compact structure, simple operation and PLC touch screen adopted, change parts can special designed by customers requirement.

Technical Parameters

Capacity	5-25(cut/inin)
Packing material pharmacy	40-120mm
PTPPTP alu foil (mm)	(0 2-0 5)x (230-270)
	(0.02-0.05)x(230-270)
Clean compressed air(pressure)	0.8-1.1 MPa
Air consumption	2.5
Power	AC380V 50Hz 6.5kw
Watercooling for moulds	reycle water with 60l/h consumption
Overall dimensions	3400x65x1450mm
Weight	2000kg

Max film width	260mm
Max packaging capacity	40-180次/分(According to its material to fix)
Suitable film thickness	0.04-0.06mm
Length of bags	50-330mm
Packaging with	25-110mm
Packaging high	5-45mm
Total power	2.7Kw 220V
Overall dimensions	3500x 880x1500mm
Weight	680kg

Capacity	80-110/^(box/min)l
Box dimension (mm)	(65-125) x (40-78) x (12-65)
Cardboard of box required	250-350g/m2
(g/m2)	
Leaflet dimension (LxW)	(80-300)x(70-210)
Cardboard of box required	250-350g/m2
Clean compressed air(pressure)	06-0.8 MPa
Air consumption	>0.3
Power	AC380V 50Hz 1kw
Overall dimensions	3100x1380x1800mm
Weight	1200kg